

WINBD Biotech **CHEM 35**

**SEMI-AUTO BIOCHEMISTRY
ANALYZER**



★ 8 FILTER +2 OPTIONAL

★ 35 IN-BUILT INCUBATOR

WINBD Biotech

WINBD Biotech

Plot No. 435, Ramgarh, Panchkula - 134118, Haryana, INDIA.
E-mail : info@winbdbiotech.com, Website : www.winbdbiotech.com
Customer Care : +91-98141 44143

★ Parameter

- Incubator: Multifunctional incubator.
- Test method: 1 point end, 2 point end, Kinetics, Fixed-time, Turbidity.
- Test mode: Flow cell & cuvette.
- Optics: 8 standard wavelengths: 340nm, 405nm, 450nm, 510nm, 546nm, 578nm, 600nm, 630nm. 2 more for optional.
- Lamp house: Long-life tungsten halogen lamp, auto-sleep function.
- Temperature: 25, 30, 37°C and Room temperature, incubator unit 37°C.
- Flow cell capacity & optical path: 32ul, 10mm.
- Resolution: 0.0001 Abs.
- Photometric range: 0.0000-3.3000 Abs.
- Display: 7.0" TFT LCD with touch screen, 800*480 pixels.
- Printer: Build-in thermal printer (30mm printer paper), support external printer.
- CPU: ARM Cortex-A8, 800MHz; DDR3 SDRAM: 512MB; Flash: 256MB.
- Memory: SD card: 8G;
Over 300 programs, 200000 results can be stored.
- Interface: USB×4, Ethernet ports×1, RS232×1.
- Operational environment: Temperature: 15°C~35°C, Humidity: 35%~85%.
- Power requirement: Wide power supply AC 100-240V, 50/60 Hz.
- Dimension: 400*300*180mm(L*W*H)



Make
the future healthy